

# VARICK

## GENERAL SPECIFICATIONS

Width	54"
Weight	15-16 oz/linear yard
Composition	85% Polyester, 15% Linen
Backing	SBR
Minimum Yardage	500 Yards
Custom Color	

## FLAME RETARDANCY SPECIFICATIONS

CAL-TB 117-2013	Passes
NFPA 260	Passes
UFAC Class 1	Passes

## PERFORMANCE SPECIFICATIONS

Abrasion	100,000+ DR
Colorfastness to Crocking	Wet: 4.5 Dry: 4.5
Seam Slippage	Fill: 69.7 Warp: 56.5
Tensile Strength	Fill: 55 Warp: 245
Tear Strength: Tongue Tear	Fill: 11 Warp: 23.2
Brush Pill	Class 5
Colorfastness to Light	Class 4.5 at 40 Hours
Cleaning Code	SW

## CLEANING INSTRUCTIONS

Spot clean with upholstery shampoo, foam from a mild detergent, or mild dry cleaning solvent. Do not saturate with liquid. Pile fabrics may require brushing to restore appearance. Cushion covers should not be removed and dry cleaned.

## RECOMMENDED APPLICATIONS



WORKSPACE



HOSPITALITY



RESTAURANT



SENIOR LIVING



\*ACT® Registered Certification Marks

## FINISHES

