

TOLSTOY

GENERAL SPECIFICATIONS

Width	54"
Weight	20 oz/linear yard
Surface Composition	100% Polyurethane (Polycarbonate)
Substrate Composition	100% Polyester
Gauge	0.040
Thickness	1.00 mm

FLAME RETARDANCY SPECIFICATIONS

CAL-TB 117-2013	Passes
NFPA 260	Passes
UFAC Class 1	Passes

REDUCED ENVIRONMENTAL IMPACT

- No added Flame Retardant Chemicals
- No added Anti-Microbial/Anti-Bacterial Chemicals
- PVC Free
- Phthalate Free
- Lead Free/Heavy Metal Free
- BPA Free/TRIS Free/Formaldehyde Free
- Does not contain Conflict Minerals
- CAB 2998 Compliant

PERFORMANCE SPECIFICATIONS

Abrasion	250,000+ DR
Colorfastness to Crocking	Wet: 5 Dry: 5
Seam Slippage	Fill: 42.9 Warp: 57.3
Tensile Strength	Fill: 113 Warp: 144
Tear Strength: Tongue Tear	Fill: 2.9 Warp: 5.1
Hydrolysis	7 weeks
Anti-Bacterial, Anti-Microbial, Mildew Resistant, Denim Dye Resistant	Passes
Cold Crack	-20°
Colorfastness to Light	200 Hours
Bleach Resistant	Yes - 20% Dilution

RECOMMENDED APPLICATIONS



*ACT® Registered Certification Marks

FINISHES