

## 1259 | FABRICS

|                                             |                           |        |
|---------------------------------------------|---------------------------|--------|
| Roll Width                                  | 140cm (+/- 3%)            |        |
| Average Roll Length                         | 30                        |        |
| Weight                                      | 724 g/ml (+/- 5%)         |        |
| Surface Composition                         | 5% Cotton + 95% Polyester |        |
| Backing Composition                         | 100% Polyester            |        |
| Abrasion Test                               |                           |        |
| EN ISO 12947-1,2                            | >65.000                   |        |
| Colour Fastness to Artificial Light         |                           |        |
| EN ISO 105-B02, Method 2 – Exposure level 6 | 5                         |        |
| Seam Slippage Resistance                    | Warp                      | Weft   |
| EN ISO 13936-2                              | 2,5 mm                    | 2,5 mm |
| Colour Fastness to Rubbing                  | Dry                       | Wet    |
| EN ISO 105-X12                              | 4-5                       | 4-5    |
| Tensile Strength                            | Warp                      | Weft   |
| EN ISO 13934-1                              | 1700 N                    | 750 N  |
| Tear Growth Resistance                      | Warp                      | Weft   |
| EN ISO 13937-3                              | 35 N                      | 25 N   |
| Snagging Test – Rotating Chamber Method     |                           |        |
| BS 8479:2008                                | 4-5                       |        |



### Natural Fabric



- Frequent wash may affect the performance of the product or its treatment (when present)
- Any stain, spills or soiling should be cleaned up promptly with a 5% neutral soap solution using a clean cloth, gently pressed and rubbing in smooth circular movements.
- In case of dry soil please remove first with a vacuum cleaner
- For articles with the Easy-to-Clean feature we recommend using a 100% cotton cloth and a soft brush if necessary
- We do not accept responsibility for any damage resulting from inappropriate use, chemical cleaning or additional impregnation.
- The analytical results are referred only to the sample tested.
- Discoloration and colour deviations tolerated by permissible industrial standards do not constitute reasons for claims.
- Colour migration may occur.
- Pilling is a natural phenomenon that occurs due to daily use and frequent washing and cannot be avoided.
- Dry cleaning is recommended to preserve the FR treatment performance.
- We reserve the right to modify, at any moment and without notice any product specifications.

