

CHAUCER

GENERAL SPECIFICATIONS

Width	54"
Weight	32 oz/linear yard
Surface Composition	100% PVC (Phthalate Free)
Substrate Composition	100% Polyester
Thickness	1.20 mm

FLAME RETARDANCY SPECIFICATIONS

CAL-TB 117-2013	Passes
NFPA 260	Passes
UFAC Class 1	Passes
FMVSS 302	Passes

REDUCED ENVIRONMENTAL IMPACT

This product does not pose any exposure risks associated with the chemicals in Prop 65

No added flame retardant chemicals

No added anti-microbial/anti-bacterial chemicals

Phthalate Free

Lead / Heavy Metal Free

BPA Free / TRIS Free / Formaldehyde Free

Does not contain conflict materials

CAB 2998 Compliant

PERFORMANCE SPECIFICATIONS

Abrasion	250,000+ DR
Colorfastness to Crocking	Wet: 5 Dry: 4.5
Seam Slippage	Fill: 45.5 Warp: 52
Tensile Strength	Fill: 92 Warp: 106
Tear Strength: Tongue Tear	Fill: 6.8 Warp: 6.1
Colorfastness to Light	300 Hours
Cold Crack	-20° F
Bleach Resistance	Yes — 20% Dilution
Stain Resistance, Sulfide Stain Resistance	Yes

RECOMMENDED APPLICATIONS



*ACT® Registered Certification Marks

FINISHES