



HENLEY

GENERAL SPECIFICATIONS

Width 54"

Weight 11-12 oz/linear yard

Composition 100% Polyester

Backing SBR

Yarn Per Inch 18 EPI 10 PPI

Yarn Size Fill: T5.5S

Warp: T9S

Minimum Yardage 500 yards

Custom Color

FLAME RETARDANCY SPECIFICATIONS

CAL-TB 117-2013 Passes

NFPA 260 Passes

UFAC Class 1 Passes

CLEANING INSTRUCTIONS

Spot clean with upholstery shampoo, foam from a mild detergent, or mild dry cleaning solvent. Do not saturate with liquid. Pile fabrics may require brushing to restore appearance. Cushion covers should not be removed and dry cleaned.

PERFORMANCE SPECIFICATIONS

Abrasion 100.000+ DR

Colorfastness Wet: 5 to Crocking Dry: 5

Seam Slippage Fill: 83.5

Warp: 84

Tensile Strength Fill: 99

Warp: 243

Colorfastness Class 5 at 40 Hours

to Light

Cleaning Code SW

Stain Resistant Yes

Brush Pill Class 5

RECOMMENDED APPLICATIONS





A次O樂的





WORKSPACE HOSPIT

HOSPITALITY RESTAURANT

*ACT® Registered Certification Marks

FINISHES

