



CANYON | PERSUASION | PHOENIX | VIBE

GENERAL SPECIFICATIONS	CANYON	PERSUASION	PHOENIX	VIBE
Width	54"	54"	54"	54"
Weight	28 oz/linear yard	28 oz/linear yard	28 oz/linear yard	28 oz/linear yard
Surface Composition	100% PVC	100% PVC	100% PVC	100% PVC
Substrate Composition	100% Polyester	100% Polyester	100% Polyester	100% Polyester
Gauge	0.040	0.040	0.040	0.040
Thickness	1.00 mm	1.00 mm	1.00 mm	1.00 mm
FLAME RETARDANCY SPECIFICATIONS				
CAL-TB 117-2013	Passes	Passes	Passes	Passes
NFPA 260	Passes	Passes	Passes	Passes
UFAC Class 1	Passes	Passes	Passes	Passes
FMVSS 302		Passes	Passes	Passes
PERFORMANCE SPECIFICATIONS				
Abrasion	250,000+ DR	250,000+ DR	150,000 DR	250,000+ DR
Colorfastness to Crocking	N/A	Wet: 5 Dry: 5	Wet: 5 Dry: 5	N/A
Seam Slippage	Fill: 30 Warp: 44	Fill: 45 Warp: 45	Fill: 32 Warp: 41	Fill: 30 Warp: 42
Tensile Strength	Fill: 60 Warp: 97	Fill: 60 Warp: 95	Fill: 62 Warp: 86	Fill: 60 Warp: 97
Tear Strength: Tongue Tear	Fill: 6.9 Warp: 5.1	Fill: 6.9 Warp: 5.1	Fill: 6.9 Warp: 5.1	Fill: 6.2 Warp: 3.1
Stain Resistant	Passes	Passes	Passes	Passes
Sulfide Stain Resistant	Passes	Passes	Passes	N/A
Cold Crack	-20°	-20°	-20°	-20°
Colorfastness to Light	650 Hours	650 Hours	650 Hours	650 Hours
Bleach Resistant	Yes - 10% Dilution	Yes - 10% Dilution	Yes - 10% Dilution	Yes - 10% Dilution
FINISHES				*Passes Anti-Microbial Mildew Resistant
RESILIENCE	✓	✓	✓	✓

RECOMMENDED APPLICATIONS



*ACT® Registered Certification Marks

CAB 2998 Compliant