

SHAGREEN

GENERAL SPECIFICATIONS

Width	54"
Weight	35-36 oz/linear yard
Surface Composition	100% PVC
Substrate Composition	75% Polyester, 25% Cotton
Gauge	0.044-0.48
Thickness	1.1-1.2 mm

FLAME RETARDANCY SPECIFICATIONS

CAL-TB 117-2013	Passes
NFPA 260	Passes
UFAC Class 1	Passes
FMVSS 302	Passes

REDUCED ENVIRONMENTAL IMPACT

- No added Flame Retardant Chemicals
- No added Anti-Microbial/Anti-Bacterial Chemicals
- Phthalate Free
- Lead/Heavy Metal
- BPA Free/TRIS Free/Formaldehyde Free
- Does not contain Conflict Minerals
- CAB 2998 Compliant

PERFORMANCE SPECIFICATIONS

Abrasion	200,000+ DR
Colorfastness to Crocking	Wet: 5 Dry: 5
Seam Slippage	Fill: 52.6 Warp: 70.9
Tensile Strength	Fill: 55 Warp: 68
Tear Strength: Tongue Tear	Fill: 14.2 Warp: 9.2
Stain Resistant, Sulfide Stain Resistant	Passes
Cold Crack	-20°
Colorfastness to Light	200 Hours
Bleach Resistant	Yes - 10% Dilution

RECOMMENDED APPLICATIONS



*ACT® Registered Certification Marks

FINISHES

