

CARLISLE WOOL

GENERAL SPECIFICATIONS

Width 54"

Weight 10 oz/linear yard

70% Wool, 20% Polyester, Composition

5% Acrylic, 5% Nylon

Yarn Per Inch 38.1 EPI 34.5 PPI

> Yarn Size Fill: MN 8.3

> > Warp: MN 8.3

400 yards

Minimum Yardage

Custom Color

FLAME RETARDANCY SPECIFICATIONS

CAL-TB 117-2013 Passes

> NFPA 260 Passes

UFAC Class 1 Passes

RECOMMENDED APPLICATIONS









WORKSPACE HOSPITALITY

RESTAURANT

SENIOR LIVING

A类O攀

*ACT® Registered Certification Marks

PERFORMANCE SPECIFICATIONS

Abrasion 75.000+ DR

Colorfastness Wet: 5 to Crocking Dry: 5

Seam Slippage Fill: 56

Warp: 86.9

Tensile Strength Fill: 57.4

Warp: 108.3

Tear Strength Fill: 7

Warp: 11.8

Colorfastness Min. Class 5 at 40 Hours

to Light

Cleaning Code SW

> Brush Pill Class 3

CLEANING INSTRUCTIONS

Spot clean with upholstery shampoo, foam from a mild detergent, or mild dry cleaning solvent. Do not saturate with liquid. Pile fabrics may require brushing to restore appearance. Cushion covers should not be removed and dry cleaned.