

ELIOT

GENERAL SPECIFICATIONS

Width	54"
Weight	18-19 oz/linear yard
Surface Composition	95% High Solid Polyurethane (Polycarbonate), 5% Silicone
Substrate Composition	100% Polyester
Gauge	0.040
Thickness	1.00 mm

FLAME RETARDANCY SPECIFICATIONS

CAL-TB 117-2013	Passes
NFPA 260	Passes
UFAC Class 1	Passes

REDUCED ENVIRONMENTAL IMPACT

This product does not pose any exposure risks associated with the chemicals in Prop 65

Phthalate Free

Lead Free

BPA Free/TRIS Free/Formaldehyde Free

Does not contain Conflict Minerals

Does not contain Flame Retardant Chemicals

Does not contain Anti-Microbial/Anti-Bacterial Chemicals

PVC Free

PERFORMANCE SPECIFICATIONS

Abrasion	100,000+ DR
Colorfastness to Crocking	Wet: 4.5 Dry: 5
Seam Slippage	Fill: 73.5 Warp: 78.5
Tensile Strength	Fill: 129 Warp: 273.2
Colorfastness to Light	Class 4 at 40 Hours
Cleaning Code	SW
Stain Resistant	Yes
Brush Pill	Class 5
Hydrolysis Resistance	15 weeks
Anti-Bacterial	Passes
Anti-Microbial	Passes
Bleach Resistant	Yes – 20% Dilution
Stain Resistant	Yes
Denim Dye Resistant	Yes
Ink Resistant	Yes
Sulfide Stain Resistant	Yes

RECOMMENDED APPLICATIONS



*ACT® Registered Certification Marks

FINISHES

