

GLAZE

GENERAL SPECIFICATIONS

Width	54"
Weight	36 oz/linear yard
Surface Composition	100% PVC
Substrate Composition	75% Polyester, 25% Cotton
Thickness	1.10 mm

FLAME RETARDANCY SPECIFICATIONS

CAL-TB 117-2013	Passes
NFPA 260	Passes
UFAC Class 1	Passes
FMVSS 302	Passes

REDUCED ENVIRONMENTAL IMPACT

No added Flame Retardant Chemicals

No added Anti-Microbial/Anti-Bacterial Chemicals

Phthalate Free

Lead/Heavy Metal

BPA Free/TRIS Free/Formaldehyde Free

Does not contain Conflict Minerals

CAB 2998 Compliant

PERFORMANCE SPECIFICATIONS

Abrasion	100,000+ DR
Colorfastness to Crocking	Wet: 5 Dry: 5
Seam Slippage	Fill: 64 Warp: 67
Tensile Strength	Fill: 78 Warp: 67
Tear Strength: Tongue Tear	Fill: 6.3 Warp: 7.1
Cold Crack	-20°
Colorfastness to Light	300 Hours

RECOMMENDED APPLICATIONS



WORKSPACE



HOSPITALITY



RESTAURANT



SENIOR LIVING



*ACT® Registered Certification Marks