



HUGO

GENERAL SPECIFICATIONS

54" Width

Weight 25.4 oz/linear yard

Composition 100% Polyurethane

> Backing 100% Polyester

Finish Writer's Block

FLAME RETARDANCY SPECIFICATIONS

CAL-TB 117-2013 Passes

> NFPA 260 Passes

UFAC Class 1 Passes

PERFORMANCE SPECIFICATIONS

Abrasion 250,000 DR

Colorfastness Wet: 5.0

to Crocking Dry: 5.0

Fill: 83.0 Seam Slippage

Warp: 83.9

Tear Strength Fill: 12.0

> Warp: 8.9 200 Hours

Colorfastness

to Light

Cleaning Code BC - Bleach Cleanable, 10% Dilution

Passes

Anti-Microbial, Anti-Bacterial,

Mildew Resistant,

Denim Dye Resistant

Hydrolysis Resistance 10 Weeks

RECOMMENDED APPLICATIONS











REDUCED ENVIRONMENTAL IMPACT

This product does not pose any exposure risks associated with the chemical in Prop 65

No added flame retardant chemicals

No added anti-bacterial / anti-microbial chemicals

Lead/ Heavy metal free

BPA free / Tris free / Formaldehyde free

Does not contain conflict minerals

*Prop 65 Compliant

*CAB2998 Compliant



