

# CONNECTION | HERITAGE | FOUNDATION

## GENERAL SPECIFICATIONS

Width	54"
Weight	30 oz/linear yard
Composition	100% PVC (Phthalate Free)
Backing	100% Polyester Brushed Knit

## FLAME RETARDANCY SPECIFICATIONS

CAL-TB 117-2013	Passes
NFPA 260	Passes
UFAC Class 1	Passes
FMVSS 302	Passes

## REDUCED ENVIRONMENTAL IMPACT

Phthalate Free (includes all Phthalates listed in CAL Prop 65 & CPSIA)

Lead Free

BPA Free/TRIS Free/Formaldehyde Free

Does not contain Conflict Minerals

CAB 2998 Compliant

## FINISHES

## PERFORMANCE SPECIFICATIONS

Abrasion	100,000+ DR
Colorfastness to Crocking	Wet: 5 Dry: 5
Seam Slippage	Fill: 50 Warp: 50
Tensile Strength	Fill: 93 Warp: 101
Tear Strength: Tongue Tear	Fill: 8 Warp: 6.8
Colorfastness to Light	300 Hours
Cold Crack	-20°
Coating Adhesion	Fill: 11.5 Warp: 10.27
Bleach Resistant	Yes - 10% Dilution
Stain Resistant	Yes

## RECOMMENDED APPLICATIONS



\*ACT® Registered Certification Marks