

CLARKE

GENERAL SPECIFICATIONS

Width	54"
Weight	20 oz/linear yard
Surface Composition	100% Polyurethane (Polycarbonate)
Substrate Composition	100% Polyester
Gauge	0.040
Thickness	1.00 mm

FLAME RETARDANCY SPECIFICATIONS

CAL-TB 117-2013	Passes
NFPA 260	Passes
UFAC Class 1	Passes

REDUCED ENVIRONMENTAL IMPACT

No added Flame Retardant Chemicals

No added Anti-Microbial/Anti-Bacterial Chemicals

PVC Free

Phthalate Free

Lead Free/Heavy Metal Free

BPA Free/TRIS Free/Formaldehyde Free

Does not contain Conflict Minerals

CAB 2998 Compliant

PERFORMANCE SPECIFICATIONS

Abrasion	300,000+ DR
Colorfastness to Crocking	Wet: 5 Dry: 5
Seam Slippage	Fill: 79 Warp: 75
Tensile Strength	Fill: 215 Warp: 125
Tear Strength: Tongue Tear	Fill: 11.9 Warp: 8.7
Hydrolysis	7 weeks
Anti-Bacterial, Anti-Microbial, Mildew Resistant, Denim Dye Resistant	Passes
Cold Crack	-20°
Colorfastness to Light	200 Hours
Bleach Resistant	Yes - 20% Dilution

RECOMMENDED APPLICATIONS



*ACT® Registered Certification Marks

FINISHES