

VERVE II

GENERAL SPECIFICATIONS

Width	54"
Roll Size	30 yards
Composition	100% Polyurethane
Backing	100% Polyester

FLAME RETARDANCY SPECIFICATIONS

CAL-TB 117-2013	Passes
NFPA 260	Passes
UFAC Class 1	Passes

PERFORMANCE SPECIFICATIONS

Abrasion	250,000+ DR
Hydrolysis	5 weeks
Cold Crack	-20°
Colorfastness to Light	200 Hours
Sulfide Stain Resistant	Passes
Bleach Resistant	10% Bleach Solution

REDUCED ENVIRONMENTAL IMPACT

- Solvent Free
- Phthalate Free
- Lead Free
- BPA Free/TRIS Free/Formaldehyde Free
- Low VOC per California Sec. 01350
- Does not contain F/R additives
- Does not contain Anti-Microbial/Anti-Bacterial additives
- CAB 2998 Compliant

CLEANING INSTRUCTIONS

Prompt cleaning is always recommended. Ordinary dirt and stains can be removed with mild soap and water. Tougher stains can be removed with a 10% bleach solution or a 50% Isopropyl Alcohol solution. Rinse the cleaned area with water and wipe dry with a lint-free cloth immediately after cleaning.

RECOMMENDED APPLICATIONS



*ACT® Registered Certification Marks