

VINTAGE

GENERAL SPECIFICATIONS

| | |
|-----------------------|---------------------------|
| Width | 54" |
| Weight | 36 oz/linear yard |
| Surface Composition | 100% PVC |
| Substrate Composition | 75% Polyester, 25% Cotton |
| Thickness | 1.10 mm |

FLAME RETARDANCY SPECIFICATIONS

| | |
|-----------------|--------|
| CAL-TB 117-2013 | Passes |
| NFPA 260 | Passes |
| UFAC Class 1 | Passes |
| FMVSS 302 | Passes |

REDUCED ENVIRONMENTAL IMPACT

No added Flame Retardant Chemicals

No added Anti-Microbial/Anti-Bacterial Chemicals

Phthalate Free

Lead/Heavy Metal

BPA Free/TRIS Free/Formaldehyde Free

Does not contain Conflict Minerals

CAB 2998 Compliant

PERFORMANCE SPECIFICATIONS

| | |
|--|------------------------|
| Abrasion | 50,000+ DR |
| Colorfastness to Crocking | Wet: 4 Dry: 4.5 |
| Seam Slippage | Fill: 65 Warp: 68 |
| Tensile Strength | Fill: 83 Warp: 67 |
| Tear Strength: Tongue Tear | Fill: 6.2 Warp: 5.6 |
| Stain Resistant, Sulfide Stain Resistant | Passes |
| Cold Crack | -20° |
| Colorfastness to Light | 300 Hours |
| Bleach Resistant | Yes - 10% Dilution |

RECOMMENDED APPLICATIONS



WORKSPACE



HOSPITALITY



RESTAURANT



SENIOR LIVING



*ACT® Registered Certification Marks