

BEEKMAN VELVET

GENERAL SPECIFICATIONS

Width	54"
Weight	18.1 oz / linear yard
Composition	100% Polyester
Finish	Resilience TX
Minimum Yardage	300 yards
Custom Color	

FLAME RETARDANCY SPECIFICATIONS

CAL-TB 117-2013	Passes
NFPA 260	Passes
UFAC Class 1	Passes

PERFORMANCE SPECIFICATIONS

Abrasion	100,000 DR
Colorfastness to Crocking	Wet: 4.5 Dry: 5
Seam Slippage	Fill: 71.4 Warp: 77.4
Tensile Strength	Fill: 259 Warp: 308
Colorfastness to Light	Class 4.5 at 40 Hours
Cleaning Code	S/SW
Stain Resistant	Yes
Brush Pill	Class 5

CLEANING INSTRUCTIONS

Spot clean with upholstery shampoo, foam from a mild detergent, or mild dry cleaning solvent. Do not saturate with liquid. Pile fabrics may require brushing to restore appearance. Cushion covers should not be removed and dry cleaned.

REDUCED ENVIRONMENTAL IMPACT

This product does not pose any exposure risks associated with the chemicals in Prop 65

Lead / Heavy Metal Free

AB 2998 Compliant - Free of Flame Retardant Chemicals

PFAS/PFC Free Stain Resistance

HPD Available

REACH Compliant

RoHs Compliant

RECOMMENDED APPLICATIONS



HOSPITALITY



RESTAURANT



WORKSPACE



SENIOR LIVING



*ACT® Registered Certification Marks

FINISHES

