

# SPECKLE

## GENERAL SPECIFICATIONS

Width	54"
Weight	24.5 oz / linear yard
Composition	88% Polyester, 7% Acrylic, 3% Polyurethane, 2% Silicone
Backing	100% Polyurethane
Finish	Supreen™ Stain and Moisture Barrier
Minimum Yardage	500 Yards
Custom Color	

## FLAME RETARDANCY SPECIFICATIONS

CAL-TB 117-2013	Passes
NFPA 260	Passes
UFAC Class 1	Passes

## PERFORMANCE SPECIFICATIONS

Abrasion	100,000+ DR
Colorfastness to Crocking	Wet: 5.0 Dry: 4.5
Seam Slippage	Fill: 124 Warp: 113
Tear Strength	Fill: 28.5 Warp: 28.2
Colorfastness to Light	Class 5
Brush Pill	Class 4.5
Cleaning Code	SW - Solvent or Spot Clean
Bleach Cleanable	Yes - 10% Dilution

## CLEANING INSTRUCTIONS

Spot clean with upholstery shampoo, foam from a mild detergent, or a mild dry cleaning solvent. Do not saturate with liquid. Pile fabrics may require brushing to restore appearance. Cushion cover should not be removed and dry cleaned. BC - Lightly Spray with a 10% dilution of household bleach and water. After the appropriate contact time, blot surface dry and wipe or rinse with fresh water and blot dry.

## REDUCED ENVIRONMENTAL IMPACT

This product does not pose any exposure risks associated with the chemical in Prop 65

- No added flame retardant chemicals
- No added anti-bacterial / anti-microbial chemicals
- Lead / Heavy metal free
- BPA free / Tris free / Formaldehyde free
- Does not contain conflict minerals
- PFAS Free
- \*Prop 65 Compliant
- \*CAB2998 Compliant

## RECOMMENDED APPLICATIONS



HOSPITALITY



RESTAURANT



WORKSPACE



SENIOR LIVING



HEALTHCARE



\*ACT® Registered Certification Marks